



YOUR FENCE COMPANY
0000 STREET ADDRESS
CITY, STATE 00000
(000) 000-0000

CHAINLINK FENCE SPECIFICATION

FABRIC: 72" 11 1/2 GA. GALVANIZED (2 1/4" Mesh) CHAIN LINK FABRIC.

TOP RAIL: 1 5/8" O.D. CQ-20 PIPE, 1.43 lbs. per foot. Top rail 21' in length, joined with 1 5/8" SLEEVE.

LINE POST: 1 7/8" O.D. CQ-20 PIPE, 1.76 lbs. per foot. Line posts set 10' on center maximum spacing. Concrete footing: 8" diameter, 30" depth.

TERMINAL POST: 2 3/8" O.D. CQ-20 PIPE, 2.30 lbs. per foot. Concrete footing: 8" diameter, 36" depth.

GATES: Framework of 1 5/8" CQ-20 PIPE, 1.43 lbs. per foot. Gates braced and trussed as necessary. Same fabric as fence.

GATE POST: 2 3/8" O.D. CQ-20 PIPE, 2.30 lbs. per foot. Concrete footing: 8" diameter, 36" depth.

FITTINGS: REGULAR BRACE BAND & CARRIAGE BOLT, PRESSED STEEL RAIL-END, PRESSED STEEL EYE-TOP, PRESSED STEEL CAP, 3/16" X 3/4" TENSION BAR, REGULAR TENSION BAND & CARRIAGE BOLT.

TIE WIRE: 6 1/2" 9 GA. ALUMINUM TIE WIRE spaced 15" on center for line posts & 24" on center for rails.

POST FOOTING: HAND MIXED CONCRETE.